

## Top Tec ATF 1400

### DESCRIPTION

Top Tec ATF 1400 is a high performance automatic transmission fluid of the new generation based on synthetic technology. It was developed specifically for use in CVTs with thrust link belt or a gear chain made of steel. The basis of modern base oils and select additives offer the best possible anti-froth protection, which is necessary for CVTs. It also features a very good stability against aging and oxidation. Top Tec ATF 1400 is tried and tested, most notably in the Mercedes-Benz A-Class and B-Class Autotronic transmissions and in continuously variable automatic transmissions (Multitronic) in Audi vehicles.

### PROPERTIES


- Excellent viscosity/temperature properties
- Best possible anti-froth protection
- Excellent low-temperature properties
- Very good aging and oxidation stability
- Outstanding protection against wear and good friction characteristics
- Optimum corrosion protection

#### **Specifications and approvals:**

**LIQUI MOLY also recommends this product for vehicles for which the following specifications are required:**

Audi/ VW G 052 180  
Audi/ VW G 052 516  
MB 236.20  
Ford CVT30 / MERCON® C  
Ford CVT23  
Toyota TC  
Hyundai SP-III  
Kia SP III  
Mitsubishi SPIII  
Mitsubishi CVTF-J1  
Nissan NS-2  
Honda HMMF  
Subaru NS-2 / Lineartronic CVTF  
Mini Cooper (EZL 7/99)  
Suzuki TC / NS-2 / CVT Green 1  
GM / Saturn DEX-CVT  
Dodge NS-2 / CVTF+4  
Jeep NS-2 / CVTF+4

**Note:** Not suitable for hybrid CVT (Honda, Ford)!



# PRODUKTINFORMATION



## TECHNICAL DATA

Density at +15 °C	: 0.851	g/cm <sup>3</sup>	DIN 51757
Brookfield viscosity -40 °C	: < 12,000	mPas	DIN 51389
Viscosity at +40 °C	: 33.0	mm <sup>2</sup> /s	DIN 51562
Viscosity at +100 °C	: 7.0	mm <sup>2</sup> /s	DIN 51562
Viscosity index	: 189		DIN ISO 2909
Flash point	: 204	°C	DIN ISO 2592
Pour point	: -48	°C	DIN ISO 3016
ASTM color	: L2,5		DIN ISO 2049

## AREAS OF APPLICATION

For the new generation of CVTs with thrust link belt or a gear chain made of steel.

## APPLICATION

The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

## AVAILABLE PACK SIZES

Top Tec ATF 1400	1 l	Part no. 3662 D-GB-I-E-P
	1 l	Part no. 8041 D-RUS-UA
	20 l	Part no. 3692 D
	205 l	Part no. 3661 D

PI 07/12/13

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

