

## Marine Engine Oil SAE 15W-40

### DESCRIPTION

Marine Engine Oil SAE 15W-40 is a universal, high-performance engine oil which is formulated in accordance with the most state-of-the-art technology. Selected base oils and a high additive content guarantee optimum lubricating action under all running conditions. The high proportion of corrosion inhibitor guarantees protection against rust and corrosion.

### PROPERTIES

- universal use for petrol and diesel engines with and without exhaust-gas turbocharging and with and without charge air cooling.
- good cold-start behaviour
- high lubricating film stability and excellent wear protection
- low evaporation losses
- high shear and ageing stability
- outstanding cleaning and dispersion properties
- prevents black sludge
- miscible with all commercially available engine oils
- outstanding corrosion protection

#### **Specifications / Approvals:**

API SL/CF/CG-4

ACEA A3-08/B4-08/E2-96 Issue 5

Volvo VDS

**LIQUI MOLY recommends this product for vehicles for which the following specifications are required**


MTU Typ 2

MAN M3275-1

### TECHNICAL DATA

Viscosity class	:	15W-40
ASTM colour	:	3
Density at 15 °C	:	0.885 g/cm <sup>3</sup>
Viscosity at 40 °C	:	108 mm <sup>2</sup> /s
at 100 °C	:	14.0 mm <sup>2</sup> /s
Viscosity index	:	137
Flash point	:	225 °C
Pour point	:	-30 °C

.../2



# PRODUKTINFORMATION



-2-

**APPLICATION** Universal engine oil for petrol and diesel engines (aspirated diesel engines and diesel engines with exhaust-gas turbocharging and with and without charge air cooler. Especially suitable for boat engines.


**INSTRUCTIONS** The engine manufacturer's operating instructions must be followed.

**AVAILABLE PACK SIZE**

Marine Engine Oil		
SAE 15W-40	5 l	Part no. 1065 D-GB-I-E-F-GR
	60 l	Part no. 1066 D

PI 08/06/11

**Our information is based on thorough research and may be considered reliable, although not legally binding.**



LIQUI MOLY GMBH  
Jerg-Wieland-Str. 4  
D-89081 Ulm-Lehr

Postfach 28 29  
D-89018 Ulm  
www.liqui-moly.de

Phone: +49-(0)731/1420-13  
Fax: +49-(0)731/1420-82  
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230  
Technische Hotline: +49-(0)731/1420-13