

Nova Super SAE 15W-40

DESCRIPTION

Nova Super SAE 15W-40 is a year-round, high-performance engine oil which is formulated according to the latest technology. Selected base oils and a high additive content guarantee optimum lubrication under extreme running conditions and during long periods between oil changes.

PROPERTIES

- Universal use for petrol and diesel engines with and without exhaust-gas turbocharging and charge air cooling.
- high lubricant-film stability and excellent wear protection
- low evaporation loss and oil consumption
- high shear and ageing stability
- outstanding cleaning and dispersion properties
- prevents black sludge
- miscible with all commercially available engine oils
- tested for compatibility with catalytic converters

Specifications / Approvals

ACEA A2-96, B3-98, E2-96 Issue 5

API CF-4/ CF/ SJ

MAN 271

Volvo VDS

Allison C-4

Caterpillar TO-2


MIL-L 2104 E

MIL-L 46152 D

LIQUI MOLY recommends this product for vehicles for which the following specifications are required:

MB 228.1

MTU Typ 1



PRODUKTINFORMATION



TECHNICAL DATA

Viscosity class	:	15W-40	
ASTM colour	:	3	
Density at 15 °C	:	0.88	g/cm ³
Viscosity at 40 °C	:	110	mm ² /s
Viscosity at 100 °C	:	14.5	mm ² /s
Viscosity index	:	132	
Flash point	:	236	°C
Pour point	:	-30	°C
Ash, Sulphate	:	1.4	g/100g
Carbon residue according to Conradson with ash	:	1.35	g/100g
Strong base number	:	10.9	mg KOH/g
Evaporation loss	:	10.0	wt %

INSTRUCTIONS

The operating instructions of the vehicle and transmission manufacturers must be followed.

AVAILABLE PACK SIZE

Nova Super		
SAE 15W-40		
	1 l	Part no. 1428 D
	5 l	Part no. 1426 D
	20 l	Part no. 1432
	60 l	Part no. 1418
	205 l	Part no. 1430

PI 10/07/13

Our information is based on thorough research and may be considered reliable, although not legally binding.

