

Top Tec ATF 1300

DESCRIPTION

Top Tec ATF 1300 is a hydraulic fluid that is largely used in units from older generations. Despite the diverse possibilities for use in automatic and manual transmissions, as well as for power steering systems and ancillaries, safe operation and perfect functioning of the units is guaranteed. Certain base oils and additive components ensure good wear protection characteristics and optimum corrosion protection.

PROPERTIES

- Outstanding viscosity and temperature characteristics
- High thermal stability
- Very good low-temperature properties
- High stability to aging
- Good wear protection characteristics
- Optimum corrosion protection

Specifications and approvals:

Ford ESW-M2C 33F

Ford ESW-M2C 33G

LIQUI MOLY also recommends this product for vehicles for which the following specifications are required:


Volvo 97330

TECHNICAL DATA

Density at +15 °C	: 0.865	g/cm ³	DIN 51757
Viscosity at +40 °C	: 35.1	mm ² /s	DIN 51562
Viscosity at +100 °C	: 7.3	mm ² /s	DIN 51562
Viscosity index	: 180		DIN ISO 2909
Pour point	: -43	°C	DIN ISO 3016
Color	: brown		

AREAS OF APPLICATION

Suitable for automatic and manual transmissions as well as for power steering systems and ancillaries in passenger vehicles and smaller commercial vehicles. Usage according to the prescribed specifications from the unit or vehicle manufacturer.



PRODUKTINFORMATION



APPLICATION


The instructions from the unit or automobile manufacturer must be followed. Top Tec ATF 1300 is also suitable for refilling systems in which ATF oils conforming to these specifications are used. Optimum effectiveness, however, is only possible when the product is used on its own (i.e. no mixing). Don't mix with oils of other specifications!

AVAILABLE PACK SIZE

Top Tec ATF 1300	1 l	Part no. 3691 D-GB-I-E-P
	20 l	Part no. 3698 D
	205 l	Part no. 3699 D

PI 02/07/11

Our information is based on thorough research and may be considered reliable, although not legally binding.



LIQUI MOLY GMBH
Jerg-Wieland-Str. 4
D-89081 Ulm-Lehr

Postfach 28 29
D-89018 Ulm
www.liqui-moly.de

Phone: +49-(0)731/1420-13
Fax: +49-(0)731/1420-82
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230
Technische Hotline: +49-(0)731/1420-13