

## Racing Gear Oil SAE 75W-90

**DESCRIPTION** Fully synthetic multi-purpose SAE class 75W-90 gear oil. High-quality synthetic base oils and special additives are used in a wide range of applications for transmissions and drives.

**PROPERTIES**

- reduces gear-shift resistance (easier to change gear)
- high efficiency
- wide viscosity range
- excellent wear protection
- low fuel consumption
- friction-reducing properties
- significant reduction in noise
- protects from rust and corrosion

Specifications and Approvals:

API GL 5  
MIL-L-2105C/D

**TECHNICAL  
DATA**

Viscosity class	: 75W-90
Density at 15 °C	: 0.870 g/cm <sup>3</sup>
Viscosity at 40 °C	: 82 mm <sup>2</sup> /s
Viscosity at 100 °C	: 14.5 mm <sup>2</sup> /s
Viscosity index	: 185
Flash point	: 184 °C
Pour point	: -43 °C
ASTM colour	: 2

**APPLICATION** For high-load transmissions and final drives.

**INSTRUCTIONS** As stipulated for gear oil. The transmission manufacturer's instructions must be followed. Miscible with mineral-base oil residues which can remain during oil changes in transmissions and drives. Can be easily disposed of with standard used oil. Optimum effect only when used alone.

**AVAILABLE  
PACK SIZE**

Racing Gear Oil	500 ml	Part no. 1516 D-GB-I-E-P
-----------------	--------	--------------------------

PI 04/03/10

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

