

## Racing Synth 4T SAE 10W-60

### DESCRIPTION

Racing Synth 4T SAE 10W-60 is a fully synthetic, high-performance engine oil developed for use in four-stroke high-performance engines for two-wheel road and racing machines. The synthetic base oils and high-quality additives satisfy and exceed the requirements of the most state-of-the-art motorbike engine designs.

### PROPERTIES


- optimum lubrication under extreme conditions
- high lubricant and ageing stability
- low oil consumption and evaporation loss
- very good wear protection
- tried and tested with exhaust catalytic converters
- suitable for wet clutches
- outstanding engine cleanliness
- miscible and compatible with commercially available engine oils.
- tested on racing machines

Corresponds to and fulfils the following classifications and specifications:

|      |     |
|------|-----|
| API  | SL  |
| JASO | MA2 |

### TECHNICAL DATA

|                     |   |                         |
|---------------------|---|-------------------------|
| Basis               | : | synthetic oil/additives |
| Viscosity class     | : | 10W-60                  |
| ASTM colour number  | : | 3.5                     |
| Density at 15 °C    | : | 0.855 g/cm <sup>3</sup> |
| Viscosity at 40 °C  | : | 155 mm <sup>2</sup> /s  |
| Viscosity at 100 °C | : | 23,8 mm <sup>2</sup> /s |
| Viscosity index     | : | 185                     |
| Flash point         | : | 240 °C                  |
| Pour point          | : | -30 °C                  |
| Evaporation loss    | : | 6.9 %                   |
| Ash, Sulphate       | : | 1.2 g/100 g             |



# PRODUKTINFORMATION



**APPLICATION** Optimum for high-stress four-stroke road and racing machines.

**INSTRUCTIONS** The operating instructions of the motorcycle and engine manufacturers must be followed.

|                                |                            |      |                          |
|--------------------------------|----------------------------|------|--------------------------|
| <b>AVAILABLE<br/>PACK SIZE</b> | Racing Synth 4T SAE 10W-60 | 1 l  | Part no. 1525 D-GB-I-E-P |
|                                |                            | 4 l  | Part no. 1687 D-GB-I-E-P |
|                                |                            | 20 l | Part no. 1527 D          |

PI 07/06/13

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

