

## Super Low-Friction SAE 10W-40

### DESCRIPTION

High-tech synthetic all-season, low-friction motor oil. Super Low-Friction was developed for the toughest requirements of modern, high-performance gasoline and diesel engines without extended maintenance intervals. Tested for use with catalytic converters and turbochargers. Saves fuel and provides optimal wear protection. The formulation has a beneficial effect on sealing materials and thus on the leaktightness of engines. That makes Super Low-Friction Motor Oil especially suitable for vehicles with mileages over 60,000.

### PROPERTIES

- Smooth engine running
- Especially suitable for vehicles with mileages over 60,000
- Beneficial effect on sealing materials and thus on the leaktightness of engines
- Rapid oil delivery at low temperatures
- High lubrication reliability at high and low temperatures
- High shear and ageing stability
- Very good wear protection
- Saves gasoline and reduces pollutant emission
- Optimum engine cleanliness
- Mixable and compatible with commercially available motor oils
- Tested with catalytic converters and performance proven with turbochargers

#### Specifications and approvals:


API	SL/CF
ACEA	A3-04/B4-04
VW	501 01/505 00 (Issue 2005)
MB-Approval	229.1

**LIQUI MOLY also recommends this product for vehicles for which the following specifications are required:**

VW	500 00
Peugeot/Citroen (PSA)	B71 2294

### TECHNICAL DATA

Viscosity class	:	10W-40	
Density at +15 °C	:	0.880	g/cm <sup>3</sup> DIN 51757
Viscosity at +40 °C	:	91.1	mm <sup>2</sup> /s      DIN 51562
Viscosity at +100 °C	:	13.7	mm <sup>2</sup> /s      DIN 51562
Viscosity index	:	152	DIN ISO 2909
Flash point	:	228	°C      DIN ISO 2592
Pour point	:	- 33	°C      DIN ISO 3016
ASTM color number	:	2.5	DIN 51578
Ash, sulphate	:	1.18	g/100 g      DIN 51575



.../2

# PRODUKTINFORMATION



## AREAS OF APPLICATION

Especially suitable for vehicles with mileages of over 60,000 as well as for use in modern gasoline, passenger vehicle diesel and turbocharged engines.

## APPLICATION

The operating instructions of the vehicle and engine manufacturers must be followed.

## AVAILABLE PACK SIZES

Super Low-Friction SAE 10W-40	1 l	Part no. 1300 D-GB-I-E-P
	1 l	Part no. 1928 D-RUS-UA
	1 l	Part no. 2454 D-NL-F- GR-ARAB
	1 l	Part no. 2624 D-PL-H-RO-TR
	1 l	Part no. 2742 GB-AUS
	1 l	Part no. 9503 D-GB-F-ARAB
	4 l	Part no. 1916 D-RUS-UA
	4 l	Part no. 2196 D-GB-I-E-P
	4 l	Part no. 2455 D-NL-F- GR-ARAB
	4 l	Part no. 2625 D-PL-H-RO-TR
	4 l	Part no. 9504 D-GB-F-ARAB
	5 l	Part no. 1301 D-GB-I-E-P
	5 l	Part no. 1858 D-NL-F-GR-ARAB
	5 l	Part no. 1929 D-RUS-UA
	5 l	Part no. 2654 D-PL-H-RO-TR
	5 l	Part no. 2743 GB-AUS
	5 l	Part no. 9505 D-GB-F-ARAB
	20 l	Part no. 1304
	60 l	Part no. 1302
	60 l	Cont. Part no. 1325
	120 l	Cont. Part no. 1326
	205 l	Part no. 1303
	1000 l	Part no. 1330
	1000 l	Cont. Part no. 4292 Export

PI 17/11/11

**Our information is based on thorough research and may be considered reliable, although not legally binding.**

