

GL 5 SAE 75W-80 Gear Oil

DESCRIPTION

GL 5 SAE 75W-80 Gear Oil is a high-performance high-pressure gear oil based on synthetic and mineral base oils and high-quality additives. Enables smooth and precise shifting action even in low temperatures. Can also be used to deal with unwanted noise and to solve gear-changing problems.

PROPERTIES

- Ideal viscosity/temperature properties
- Excellent low-temperature properties
- Outstanding aging and oxidation stability
- Suitable for eliminating shifting problems
- Outstanding protection against wear and good friction characteristics
- Very good corrosion protection behavior

Specifications and approvals:

API GL 5

MIL-L 2105 C

LIQUI MOLY also recommends this product for vehicles for which the following specifications are required:


PSA B71 2330

TECHNICAL DATA

Density at +15 °C	: 0.880	g/cm ³	DIN 51757
Viscosity at -40 °C	: < 150,000	mPas	DIN 51389
Viscosity at +40 °C	: 53.5	mm ² /s	DIN 51562
Viscosity at +100 °C	: 8.45	mm ² /s	DIN 51562
Viscosity index	: 132		DIN ISO 2909
Flash point	: 200	°C	DIN ISO 2592
Pour point	: -43	°C	DIN ISO 3016
ASTM color	: L 2.5		DIN ISO 2049

AREAS OF APPLICATION

Specially developed for use in Peugeot and Citroen manual transmissions. Can also be used in other manual transmissions to deal with unwanted noise and to solve gear-changing problems. Usage according to the prescribed specifications from the unit or vehicle manufacturer.



.../2

PRODUKTINFORMATION



APPLICATION


The specifications and instructions from the unit or vehicle manufacturer must be followed. Optimum effectiveness is only possible when the product is used unmixed.

AVAILABLE PACK SIZES

GL 5 SAE 75W-80 Gear Oil	1 l	Part no. 3658 D-GB-I-E-P
	1 l	Part no. 7619 D-RUS-UA

PI 01/08/10

Our information is based on thorough research and may be considered reliable, although not legally binding.



LIQUI MOLY GMBH
Jerg-Wieland-Str. 4
D-89081 Ulm-Lehr

Postfach 28 29
D-89018 Ulm
www.liqui-moly.de

Phone: +49-(0)731/1420-13
Fax: +49-(0)731/1420-82
e-mail: info@liqui-moly.de

Service Hotline: 0800/8323230
Technische Hotline: +49-(0)731/1420-13