

Longtime High Tech SAE 5W-30

DESCRIPTION

Top-quality, state-of-the-art, low-friction motor oil for use all year round. The combination of unconventional basic oils using synthetic technology, together with the latest additive technology, guarantee a motor oil that provides exceptional protection against wear and reduces oil and fuel consumption, while ensuring that the engine is immediately supplied with oil. This product allows for oil change intervals of up to 40,000 km, depending on the manufacturer's specifications. Longtime High Tech 5W-30 is best suitable for gas fuelled (CNG/LPG) passenger cars.

PROPERTIES

- Smooth engine running characteristics
- Long engine service life due to exceptional protection against wear
- Rapid oil delivery at low temperatures
- Optimum oil pressure at all engine speeds
- Premium lubrication reliability at high and low temperatures
- High shear and ageing stability
- Reduces fuel consumption and pollutant emissions
- Outstanding engine cleanliness
- Tested with catalytic converters and performance proven with turbochargers
- Mixable and compatible with commercially available motor oils.

Specifications / Approvals:


ACEA	C3
API	SN / CF
BMW	Longlife-04
Ford	WSS M2C 917-A
MB-Approval	229.51
VW	502 00 / 505 00

LIQUI MOLY recommends this product for vehicles for which the following specifications are required:

ACEA	A3 / B4
MB	229.31
VW	505 01

TECHNICAL DATA

Viscosity class	: 5W-30	
Density at +15 °C	: 0.855	g/cm ³ DIN 51757
Viscosity at +40 °C	: 71,5	mm ² /s DIN 51562
Viscosity at +100 °C	: 12.0	mm ² /s DIN 51562
Viscosity index	: 165	DIN ISO 2909
Flash point	: 230	°C DIN ISO 2592
Pour point	: - 39	°C DIN ISO 3016
ASTM color	: L2.5	DIN ISO 2049
Ash, sulphate	: 0.80	g/100 g DIN 51575



PRODUKTINFORMATION



APPLICATIONS

Optimum for modern gasoline and diesel engines with multi-valve technology, Valvetronic and turbocharging (with or without charge air cooling). Especially suitable where there are long intervals between oil changes and heavy duty engine requirements.

APPLICATION

The operating instructions of the vehicle and engine manufacturers must be followed.

Full effectiveness can only be ensured when the product is not mixed!

AVAILABLE PACK SIZE

Longtime High Tech
SAE 5W-30

1 ltrs	Part no. 1136 D-GB-I-E-P
1 ltrs	Part no. 2038 GB-F-E-USA-CAN
1 ltrs	Part no. 7563 D-RUS-UA
1 ltrs	Part no. 8978 D-NL-F-GR-ARAB
1 ltrs	Part no. 9506 D-GB-F- ARAB
4 ltrs	Part no. 1144 D-GB-I-E-P
4 ltrs	Part no. 7537 D-RUS-UA
5 ltrs	Part no. 1137 D-GB-I-E-P
5 ltrs	Part no. 2039 GB-F-E-USA-CAN
5 ltrs	Part no. 8981 D-NL-F-GR-ARAB
5 ltrs	Part no. 7564 D-RUS-UA
5 ltrs	Part no. 9507 D-GB-F- ARAB
20 ltrs	Part no. 1138 D
60 ltrs	Part no. 1139 D
205 ltrs	Part no. 1140 D
Bulk goods	Part no. 1141

PI 14/06/13

Our information is based on thorough research and may be considered reliable, although not legally binding.

