

Super HD Turbo Plus

DESCRIPTION

Super HD Turbo Plus is a year-round, multi-purpose engine oil which is suitable for efficient lubrication in a mixed vehicle fleet. Due to the combination of selected agents and mineral base oils, this product is suitable for use in both diesel and petrol engines.

PROPERTIES

- universal use in petrol and diesel engines with and without exhaust-gas turbocharging
- high lubricating-film stability and good wear protection
- low evaporation losses
- high shear and ageing stability
- good cleaning and dispersion properties
- miscible with all commercially available engine oils
- tested for compatibility with catalytic converters


Specifications / Approvals:

API SF/CD
CCMC G4, D2, PD-2
MIL-L-46 152 B
MIL-L-2104 C

TECHNICAL DATA

Viscosity class	:	15W-40
Colour according to ASTM	:	4
Density at 15 °C	:	0.88 g/cm ³
Viscosity at 40 °C	:	108 mm ² /s
Viscosity at 100 °C	:	14.5 mm ² /s
Viscosity index	:	135
Flash point	:	224 °C
Pour point	:	-28 °C
Ash, Sulphate	:	0.9 g/100g
Strong base number	:	6.5 mgKOH/g
Evaporation loss	:	11.5 wt %

.../2



PRODUKTTINFORMATION



APPLICATION Used as a universal oil for petrol and diesel engines with and without turbocharging.

INSTRUCTIONS The operating instructions of the vehicle and engine manufacturers must be followed. Can be mixed with all commercially available engine oils. Fully effective only when used alone.

AVAILABLE PACK SIZE	Super HD Turbo Plus	1 l canister	Part no. 4735
		5 l canister	Part no. 4736
		60 l drum	Part no. 4739
		205 l drum	Part no. 4738

PI 03/06/05

Our information is based on thorough research and may be considered reliable, although not legally binding.

