

Top Tec ATF 1200

DESCRIPTION

Top Tec ATF 1200 is an automatic gear oil from the latest generation based on synthetic HC base oils in combination with the latest high-performance additives. The outstanding composition of various base oil and additive components ensures optimum stability to aging, excellent protection against wear and good friction characteristics. Top Tec ATF 1200 conforms to the requirements of numerous unit and vehicle manufacturers and guarantees perfect operation of the units even under extreme operating conditions and when exposed to large temperature fluctuations. Also suitable for extended oil change intervals.

PROPERTIES

- Outstanding viscosity/temperature characteristics
- Very high thermal stability
- Excellent low-temperature properties
- Optimal stability to aging and high chemical resistance
- Outstanding protection against wear and good friction characteristics
- Outstanding corrosion protection
- Multi-purpose

Specifications and approvals:

GM Dexron IIIH

Mercon V

JASO 1-A

Toyota Type T-II / T-IV

Allison C4, TES 295

Nissan Matic Fluid, D, J, K

Kia SP II / SP III

Mitsubishi SP II / SP III

Hyundai SP II / SP III

Mazda ATF M III / ATF M V

Honda ATF Z1 (without CVT's)

LIQUI MOLY also recommends this product for vehicles for which the following specifications are required:

Dexron VI

JWS 3309 (Aisin Warner)

Chrysler ATF +3, +4

MB 236.1, 236.2, 236.5, 236.6, 236.7, 236.9, 236.10, 236.11

Daimler NAG-1

BMW LT 71141, LA 2634, 7045 E, 8072-B

MAN 339 Typ Z1, Z2

MAN 339 Typ V1, V2

ZF TE-ML 02F, 03D, 04D, 05L, 09, 11A, 11B, 14A, 14B, 16L, 17C


Voith H 55 6336.xx

VW G 052 162

VW G 055 025

Volvo 97340 / 97341

Subaru ATF



.../2

PRODUKTINFORMATION



TECHNICAL DATA

Density at +15 °C	: 0.850	g/cm ³	DIN 51757
Brookfield viscosity -40 °C	: 12000	mPa x s	DIN 51389
Viscosity at +40 °C	: 33.6	mm ² /s	DIN 51562
Viscosity at +100 °C	: 7.1	mm ² /s	DIN 51562
Viscosity index	: 181		DIN ISO 2909
Flash point	: 210	°C	DIN ISO 2592
Pour point	: -50	°C	DIN ISO 3016
ASTM color	: red		DIN 51578

AREAS OF APPLICATION

For automatic transmissions, manual transmissions, steering systems, hydraulic systems and auxiliary drives both in passenger vehicles and commercial vehicles and in industrial applications. Usage according to the prescribed specifications from the unit or vehicle manufacturer. Universally applicable in European, American and Asian cars.

APPLICATION

The specifications and instructions from the unit or vehicle manufacturer must be followed. Top Tec ATF 1200 can also be used for refilling systems in which traditional ATF oils are used. Optimum effectiveness, however, is only possible when the product is used on its own (i.e. no mixing).

AVAILABLE PACK SIZE

Top Tec ATF 1200	500 ml	Part no. 3680 D-GB-I-E-P
	1 l	Part no. 2393 D-GB-F-ARAB
	1 l	Part no. 3681 D-GB-I-E-P
	1 l	Part no. 7502 D-RUS-UA
	5 l	Part no. 3682 D-GB-I-E-P
	5 l	Part no. 8040 D-RUS-UA
	20 l	Part no. 3683 D
	60 l	Part no. 3684 D
	205 l	Part no. 3685 D
	Bulk oil	Part no. 3686 D

PI 11/06/13

Our information is based on thorough research and may be considered reliable, although not legally binding.

